

Marked-up copy of the specification

FUEL CELL WITH FUEL DELIVERY DEVICE AND METHOD OF MANUFACTURE

TECHNICAL FIELD

The present invention relates to the field of integrated circuits, and in particular to the field of integrated circuit containing an integrated fuel cell.

~~This invention relates to a fuel cell with a fuel delivery device according to the features of the preamble of Claim 1, a circuit with an integrated fuel cell of this type, an electrically operated device with such a fuel cell, a method for manufacturing such a fuel cell, and a sensor device.~~

BACKGROUND OF THE INVENTION

The electrical power for electrically operated devices, circuits, and the like, is ordinarily supplied by external energy sources. Typical external energy sources are connections to a power network or, ~~batteries, or storage batteries.~~

Fuel cell systems can also be used instead of ~~batteries or storage batteries.~~ Fuel cells ~~ordinarily consist of~~ typically include a first electrode system and a second electrode system, one of which serves as an anode and the other as a cathode. ~~Between the two electrode systems there is a~~ A membrane-electrode unit (MEU) with catalytic properties is located between the electrodes and that serves as a proton-permeable membrane with catalytic coating. Such a fuel cell also has a fuel delivery device for feeding in a fuel, typically hydrogen, and a reactant delivery device for feeding in a reactant. The reactant reacts with protons that originate from the fuel and that have passed through the membrane, to generate current.

U.S. Patent 6,312,846-B1 discloses a fuel cell ~~that is formed~~ on a semiconductor wafer, with channels ~~being formed~~ in the wafer as conductors for the fuel and for the reactant, and with

a membrane ~~being~~ formed between the channels that permits the diffusion of protons. It is a drawback to such systems that an additional separate reservoir connected to the channel conducting the fuel has to be provided.

U.S. Patent 6,326,097-B1 discloses a system designed to recharge the batteries, for example of a mobile radio. This system ~~consists essentially of~~includes a mount with an electrical connection for the instrument to be provided with current and a fuel cell system to generate the current to be supplied, as well as a fuel delivery device to feed the fuel into the fuel cell system. The fuel delivery device in this case ~~consists of~~includes a receptacle for hydrogen storage cartridges, which can be replaced after the fuel is consumed. Such systems are structurally complex and are reasonable for generating a rather large amount of current, for example, as needed by mobile radios, ~~for example.~~

Also generally known from U.S. Patent 6,160,278 and International Application WO 01/69228 A2 are hydrogen sensors that are fabricated as semiconductor structural units. Palladium (Pd) is used here as the hydrogen-sensitive electrode material.

~~The goal of this invention consists of providing~~ There is a need for a fuel cell with a fuel delivery device and/or a reactant delivery device that has a simple structure and is designed to provide a given amount of current, or the minimum amount required.

SUMMARY OF THE INVENTION

~~This goal is achieved by a fuel cell with a fuel delivery device according to the features of Claim 1 and a method for manufacturing such a fuel cell with the features of Claim 13. Such a fuel cell can advantageously be an integrated component of a circuit and/or of an electrically operated device according to the features of Claims 6 or 8.~~

A fuel cell comprises a first and a second electrodes, a proton permeable layer, a fuel delivery layer and a reactant delivery layer. The first and the second electrodes are configured to define a reaction region, where the first electrode configured as a cathode and the second electrode configured as an anode. The proton permeable layer is positioned between the first and the second electrodes. The fuel delivery device is configured to provide fuel to the first electrode. The reactant delivery device is configured to provide reactant to the second electrode, where the reactant reacts with protons from the fuel to generate a current. Where the fuel penetrates into the first electrode.

~~The starting point is a fuel cell includes with a first electrode and a second electrode, one of which is made as the cathode and the other as the anode, and a layer with catalytic activity that is permeable to at least protons or additional catalytic material in the region between the first electrode and the second electrode. The fuel delivery device also includes a for the infeed of a fuel infeed, and a reactant delivery device for the infeed of a reactant that reacts with protons from the fuel to generate current, with the fuel delivery device and the reactant delivery device being located on the side of the first electrode and on the side of the second electrode, respectively.~~

Using, as the fuel delivery device, a layer integrated into the fuel cell into which the fuel is already incorporated provides the benefit that no separate fuel infeed channels or the like have to be provided. This simplifies construction considerably.

According to an alternative embodiment, a fuel cell is provided with a reactant delivery device according to the features of Claim 14.

It is advantageous also to provide sensor devices with the features of Claim 25.

Advantageous refinements are the objects of dependent claims.

The fuel delivery device ~~suitably may include~~ consists of a material contacted by the fuel that releases the fuel or protons generated from it as needed. Palladium is preferably used as the base material for such a fuel delivery device because of its good hydrogen sensitivity, with hydrogen usually being used as the fuel for fuel cells at the present time.

In some examples, ~~The the preferred~~ reactant is oxygen, which can be fed in from the atmosphere. The reactant infeed device in the simplest case is therefore a channel or an open surface that communicates with the external space.

~~It is especially advantageous to use a~~ A control device may be used to activate the fuel cell or a unit ~~that includes~~ consisting of multiple coupled fuel cells of this type. Such a control device on the one hand can be a switch that closes a circuit between the two electrodes of the fuel cell. On the other hand, in ~~a particularly preferred~~ another embodiment, a fuel cell can be provided in which the reactant delivery device ~~includes~~ consists of a space that has no reactant, or for example that is evacuated of ambient air. The control device, for example, ~~can then~~ includes ~~consist of~~ a window to this evacuated space that can be opened to permit the entry of ambient air and with it oxygen as the reactant, to the fuel cell or its corresponding reaction surface.

The control device, for example, can have a control element such as the switch or the partition to be opened, to trigger an alarm. Alarm devices of this type can be used in many ways, especially to signal a burglary or to signal an emergency for a handicapped person. The alarm signals can be emitted in the usual way, in particular by light signals, acoustic signals, or by radio transmission to an emergency control center. In the latter case, besides transmitting the actual emergency signal, it is desirable also to transmit personal data about the sender and preferably a current position determined, for example, by a GPS (global positioning system).

It is also possible to use such fuel cells as energy reservoirs for recharging electrically operated circuits or devices that consume only minimal current, so that connecting a battery or providing a fuel reservoir can be structurally omitted.

Such a fuel cell with a fuel delivery device can advantageously be integrated directly into a circuit. An advantageous area of use would be CMOS circuits. Use in appropriate electrically operated devices is also advantageous instead of using a battery. An example of such an electrically operated device can be an alarm system in which the fuel cell is replaced after single or multiple activations of an alarm.

Modular construction that permits replacement as a module after one or more uses is particularly advantageous. Such a module may ~~include~~ consist of only a fuel cell with its fuel delivery device, but, for example, may also ~~include~~ consist of a circuit with an integrated fuel cell. Such a module advantageously has connectors, for example plugs that can be inserted into corresponding sockets of a circuit or of an electrically operated device.

Connection of a fuel sensor, especially a hydrogen sensor, is also advantageous for such a fuel cell, with the fuel sensor being in contact with the layer that contains the fuel. A warning signal can be emitted by the fuel sensor in case of decreasing fuel content, which shows that the fuel cell has to be replaced.

Depending on the choice of parallel or series circuitry, coupling multiple fuel cells of this type makes it possible to increase the available current and/or voltage. In this case, multiple fuel cells can be placed on one chip face, and can be wired in parallel through a common multiplex cable.

The fuel cells may also be easily recycled ~~Since~~ such cells are structural units made of single pure materials, ~~these fuel cells can also be easily recycled.~~

The above advantages are also obtained correspondingly for the case of a reactant delivery device. Ideally, such a fuel cell can also have both a fuel delivery device and a reactant delivery device.

Hydrogen is preferably considered as the fuel and oxygen as the reactant. However, any other fuels and appropriate reactants can also be used. In particular, the terms fuel and reactant should be interpreted broadly, for example, with where oxygen in the last analysis also to be viewed as the fuel and hydrogen as the associated reactant, ~~for example.~~

Embodiments are also possible in which both the fuel and the reactant are provided in the electrodes or in materials adjacent to the electrodes.

BRIEF DESCRIPTION OF THE DRAWINGS

~~Exemplary embodiments will be described below in further detail with reference to the drawings:~~

FIG. ~~figure~~ 1 ~~shows~~ illustrates a fuel cell with fuel delivery device mounted on an integrated circuit on a base in simple form;

FIG. ~~figure~~ 2 illustrates ~~shows~~ a fuel cell in a preferred embodiment in combination with a circuit;

FIG. ~~figure~~ 3 illustrates ~~shows~~ another circuit arrangement with a fuel cell and a circuit in a reactant-free space;

FIG. ~~figure~~ 4 illustrates ~~shows~~ an alternative embodiment with an alternative electrode structure; and

FIG. ~~figure~~ 5 illustrates ~~shows~~ another embodiment with yet another electrode structure and wiring as a sensor.

DETAILED DESCRIPTION

Referring to FIG. 1, ~~As Figure 1 shows,~~ a fuel cell 1 ~~includes~~ consists essentially of a first electrode 3 and a second electrode 4, or an appropriate electrode system. The two electrodes 3, 4 are formed at least by one proton-permeable layer 5, preferably in the form of a catalytic membrane. The electrodes 3, 4 are formed as anode and cathode, respectively, and have electrical connections 8. In the ~~exemplary embodiment shown~~ present example, the first electrode 3 is positioned directly on a base 2, so that a direct connection can be made to a corresponding conductive region of the base 2. A contact 8 ~~is made in the form of a conductor line that leads from the second electrode 4 to the surface of the base 2, for example to connect the second electrode 4.~~ The base 2, in ~~an especially preferred embodiment~~ some examples, ~~consists~~ includes on its top, i.e. facing the fuel cell 1, of a polysilicon 6 with appropriate structuring or design of appropriately doped regions. The polysilicon 6 constitutes a transition layer to an integrated circuit 7 (IC) located beneath it that is to be supplied with current from the fuel cell 1.

~~As is customary for fuel cells, fuel~~ Fuel that ~~preferably consists of~~ includes hydrogen H_2 escapes from the face of the first electrode 3. The fuel reacts with the catalytic layer 5 or appropriate elements in the material of the first electrode 3 in such a way that hydrogen ions, i.e. protons, are released. These protons pass through the proton-permeable layer 5 toward the second electrode 4. In the region of the second electrode 4, the protons react with a reactant fed to this region, preferably oxygen O_2 . When a circuit is closed between the electrical conductors 8, a corresponding current flows through them.

~~As Figure 1 shows~~FIG. 1 illustrates one example where, the reactant O_2 arrives directly at to the freely accessible second electrode 4 from the surroundings, so that with regard to such that the reactant operation is possible in any area with oxygen-containing air. ~~In the embodiment shown~~In the present example, the second electrode 4 ~~includes~~consists of a diffusion layer that permits the entry and passage of the reactant O_2 .

The fuel delivery device advantageously ~~includes~~consists directly of the first electrode 3 itself and/or another layer adjacent to it. This first electrode 3 or the other layer contains fuel, i.e. preferably for example hydrogen H_2 . When needed, ~~this the~~fuel is released from the material of the first electrode 3, in a comparable manner to what is known otherwise from prior art fuel cells from corresponding fuel infeed channels.

~~Actually, at first glance such a system appears disadvantageous since only a limited amount of fuel is available, but the~~The structural advantage of and the capability of the small size of the system outweighs this, ~~especially~~the limited amount of available fuel. This may also be true in devices with ~~only~~very low ~~and perhaps,~~ for example ~~only~~a one-time, current demand, since no additional fuel infeed channels or separate fuel reservoirs are necessary.

~~The manufacture of such~~Manufacturing a fuel cell with the integrated fuel delivery device is particularly simple in a semiconductor production process, for example in a CMOS process (~~CMOS: complementary symmetry metal oxide semiconductor transistor~~). In ~~this ease~~the present example, a material treated by the fuel is applied to a base layer in the preparation of the layer to develop the first electrode 3 or the other layer adjacent to it. A combination of contacted palladium (Pd) that is treated with hydrogen during or after the deposition process ~~is especially~~may be advantageous. The membrane or the proton-permeable layer 5 and other materials and layers necessary for a fuel cell are then applied.

For example, ~~thea~~ first electrode 3 ~~that includes~~ consisting of a palladium layer with an area of 1 mm^2 and $1 \text{ }\mu\text{m}$ thick can be saturated with hydrogen during the production process. ~~The preferred objective with such a system is to manage with this hydrogen, in other words not to provide for any additional infeed devices for hydrogen or corresponding energy carriers.~~ In one example, no other additional infeed devices for hydrogen or corresponding energy carriers is provided. The oxygen is advantageously fed in from the atmosphere. ~~According to initial calculations.~~ In another example, a current of $1 \text{ }\mu\text{A}$ lasting ten seconds can may be generated by a single treatment with hydrogen ~~in the example described.~~ Simple semiconductor circuits or chips, for example an alarm system, may ~~can~~ be provided with an integrated power source ~~in this way, for example to make an alarm system.~~

~~Thus,~~ In one example, the system is used ~~use for in~~ circuits and devices ~~to be used preferably in emergencies is particular advantageous. A system for this purpose is shown in FIG. figure 2 by way of example.~~

~~FIG. figure 2 shows that not only the integrated system of a fuel cell 1 with a base 2 described above is possible, but also~~ illustrates an example of a modular system ~~of having~~ a replaceable fuel cell 1 that can be plugged into a base 12. The fuel cell 1, for example, in this case again ~~includes~~ consists essentially of the structure described above, so that comparable structural elements need not be discussed again.

Electrical conductors that are ~~preferably located,~~ for example, on the sides of the electrodes 3, 4 ~~in the illustrated exemplary embodiment and are designed as contact pins 11,~~ again serve to connect the first and second electrodes 3, 4. These The contact pins 11 lead downward toward the base 12 made as a bottom plate, and pass into and through this base 12 through contact pin receptacles or holes 13. Contacts 14 that make contact between

corresponding electrical conductors 15 on or in the base 12 and the contact pins 11 are present in the area of each hole 13. The holes 13 and/or the contacts 14 are of such dimensions and/or are provided with such material, for example, that they offer enough support for the contact pins 11 so that the fuel cell 1 can be positioned removably but sufficiently firmly on the base 12 through the contact pins 11.

~~In the exemplary embodiment illustrated, the~~ The fuel cell 1 serves to supply current to a circuit 16, which is likewise placed on the base 12. The circuit 16 here is supplied with current through the two electrical conductors 15. One of the two conductors 15 leads ~~in this case~~ through a switching device 17, which can be designed, for example, as a simple pushbutton. However, any other form of switching device, in particular light sensor switches, switching devices reacting to acoustic signals, motion detectors, and the like, is also possible as a switch. After activation of the switching device 17, the circuit is closed and the electrochemical process in the fuel cell is activated to supply the circuit 16. Hydrogen H_2 , for example, ~~that is~~ present in the material of the first electrode 3 or in a layer adjacent to it is cleaved, and protons pass through the proton-permeable layer 5 to the second electrode 4, where a reaction with oxygen O_2 from the atmosphere takes place, with current being generated.

If the circuit 16 is, for example, an alarm system ~~for example~~, then an alarm can be triggered by the activation of the switching device 17, for example by sounding a warning tone, a light signal, or by transmitting an electromagnetic signal through a radio interface or a wired interface to a receiver, for example in an emergency center.

In addition to the warning information, such a signal can also transmit coded information about the transmitter or its holder, or place of installation, and preferably also position data when

used as a portable warning device. Current position information can be provided, for example, by coupling with a GPS receiver.

Alternatively to fastening the fuel cell on the base 12 through the contact pins 11, additional or different fasteners can also be provided. ~~In particular, it is also possible to~~In one example, the fuel cell 1 is fastened ~~the fuel cell 1~~ to biosensors and the like.

The system advantageously also has a fuel sensor 18, ~~preferably for example~~ a hydrogen sensor, to determine the content or residual content of fuel in the first electrode 3 or in a layer adjacent to it, or both. ~~Such a~~The fuel sensor 18 includes ~~consists, for example, of an ISFET~~ (ion-selective field effect transistor) with an applied palladium Pd layer or a palladium resistor. This fuel cell sensor 18 is connected by appropriate leads to other circuit components that serve to signal fuel depletion, so that the fuel cell can be replaced as needed.

~~Instead of the~~such a fuel cell sensor 18 or in addition to it, however, a circuit that measuresIn one example, the remaining fuel is determined by a circuit that measures the resistance of the fuel delivery device and compares the measurement with test measurements previously made ~~previously can also be used to determine the remaining fuel.~~

~~Another exemplary embodiment is shown in FIG. 3~~ illustrates another example of a fuel cell system. Elements that are structurally identical or equivalent with reference to the above exemplary embodiments are not mentioned again. ~~In essence, the embodiment has~~The system comprises a base 12 on which ~~are~~is mounted a fuel cell 1 with a first electrode 3 containing fuel, a proton-permeable layer 5, and a second electrode 4 mounted on a base 12. Electrical conductors 8, 15 lead from the fuel cell 1 to a circuit 16, likewise positioned on the base 12. ~~This can be either~~The circuit 16 may be, for example, an alarm system, a sensor, a storage device, or the like, ~~for example.~~ In contrast to the ~~second exemplary~~

~~embodiment~~previous embodiment, this system does not have an ordinary switching device that disconnects at least one of the two electrical conductors 15 in the normal state. Instead, the entire system is in a housing 20 whose internal space is free of the reactant necessary for generating current. In the usual example, there would be no oxygen inside the housing 20. To activate the generation of current, there is a region that is closed off in normal operation inside one of the walls of the housing 20, which serves as a switching device 27. By opening this closed-off region, ~~preferably for example~~ by a film that can be pierced or a valve to be opened, atmospheric air and thus oxygen enters the internal space of the housing 20. ~~This~~The opening leads to activation of the electrochemical process and thus to a flow of current through the circuit 16. ~~According to an especially preferred form of embodiment~~In another example, the internal space of the housing 20 is evacuated, so that when the switching device 27 is opened all at once or by using the controllable valve in a controlled manner, atmospheric air enters the previously evacuated internal space of the housing 20. Activation of current generation ~~can~~may be ~~hastened by this~~expedited in this manner.

~~In the simplest form of embodiment, however~~In another example, the switching device 27 ~~includes~~can also consist of a removable housing or a peelable film that can be formed around the entire system or only around the second electrode 4 or the region in which the reactant can react with the protons.

FIG. figure 4 illustrates an alternative electrode system. Instead of a one-piece electrode 4 ~~that includes~~consisting of a diffusion layer, the electrode ~~includes~~consists of multiple parts, for example a diffusion layer 4* and an actual electrode covering 4**. The electrode covering 4** ~~includes~~consists of a solid electrically conductive material and serves to feed in current or to

divert it. The diffusion layer 4* allows the reactant O₂ to enter from the side or appropriate openings in the electrode covering 4**.

FIG. 5 illustrates another example of an electrode system. The entire electrode 4° ~~includes~~ consists of a material that is a good electrical conductor, but which does not allow the passage of the reactant O₂, or allows it only inadequately. Reactant channels 4⁰⁰ or other passages in the electrode serve to feed the reactant O₂ to the proton-permeable layer membrane-electrode unit 5, for example a membrane-electrode unit (MEU) with catalytic properties. The reactant channels 4⁰⁰ are preferably formed adjacent to the proton-permeable layer membrane-electrode unit 5.

Only structural elements relevant to the principal mode of operation are outlined in the illustrated exemplary embodiments. Other functionally necessary structural elements are to be used in accordance with the knowledge of the individual skilled in the art. For example, a coating that insulates from the reactant can be formed around the lower region of the fuel cell so that access of reactant from the atmosphere to the first electrode ~~can~~ may be prevented.

While the above exemplary embodiments are described with a layer delivering the fuel, a layer that delivers the reactant can be formed in addition or alternatively in a corresponding manner, with the fuel then being fed in from the outside.

The structure for this is then essentially as described above. Instead of the fuel, in the present case hydrogen H₂, the reactant, in the present case in particular oxygen O₂, is then introduced into a layer. Appropriately, the reaction region and any region present with a layer that contains fuel ~~is~~ are shielded so that no other reactant can penetrate from the outside and trigger the current-producing process.

Accordingly, the fuel is ~~then~~ fed in from the outside for operation. In case of a combined method with a layer that feeds in the fuel and one that feeds in reactant, an appropriate switching device is made available that begins the electrochemical reaction after actuation and makes current available.

Such a fuel cell can also be used ~~advantageously~~ as a sensor to determine the amount of reactant available in the surroundings. As ~~FIG. 5 shows~~ FIG. 5 illustrates, the strength of the current generated by the fuel cell is measured, for example, by a measuring device 30. The current is in a direct ratio to the amount of reactant that reaches the fuel cell from the surroundings.

Sensors can thus be used to determine the quantity of a reactant in the surroundings of the fuel cell by determining the amount of current or the voltage of the current generated, and displaying or interpreting this.

~~Such a sensor can be used not only to indicate a given condition of the surroundings.~~
Naturally, ~~hydrogen~~ Hydrogen ~~can~~ may also be considered to be a reactant, with the function of fuel then being taken over by oxygen.

A sensor may also indicate a given condition of the surroundings. ~~For~~ In one example, the sensor ~~can also be~~ is used as a warning device, for example to warn of gases containing carbon that do not ordinarily occur in this environment or should not occur for safety reasons. The use of the described layers with integrated fuel or reactant is particularly advantageous in such warning devices. In the usual case, for example, an alarm needs to be triggered only in the emergency of a gas leak. Such warning devices equipped with an external fuel infeed would be uneconomical for this reason. Such a sensor with the integrated reactant or fuel for a limited

operating time can thus be used to advantageously, especially in areas in which current or fuel is rarely or never needed only rarely, or never in the under normal ease conditions.

~~However, such~~In other examples, sensors ~~can may also be used advantageously in~~
 combination with an external fuel or reactant infeed device. A sensor to which the fuel or the
 reactant is fed continuously through a rechargeable or replaceable gas cartridge or through a
 fixed installed line can be used to great advantage to measure correspondingly the reactant or the
 fuel in the surroundings. ~~On the one hand~~In another example, ~~this the~~ infeed device ~~can may~~
 make permanent operation possible as a sensor. ~~On the other hand~~In another example, ~~it can also~~
~~be assured that the~~ infeed of fuel or reactant ~~occurs may occur~~ continuously so ~~that to avoid~~
~~variations are avoided,~~ and conclusions can be drawn about the intensity of the reactant or the
 fuel in the surroundings from variations of the measured current strength or voltage, directly and
 without a second variable parameter.

Although the present invention has been shown and described with respect to several
 preferred embodiments thereof, various changes, omissions and additions to the form and detail
 thereof, may be made therein, without departing from the spirit and scope of the invention.

What is claimed is: